

OIL SUCTION & DISCHARGE 150PSI



Tank truck and tank wagon suction and delivery hose, it withstand the full vacuum, used for wide range of petroleum products up to 50% aromatic content.

INNER TUBE	Seamless oil resistant nitrile rubber
OUTER COVER	Weather and abrasion resistant neoprene rubber
REINFORCEMENT	Multi layers of close mesh textile cords with embedded steel wire helix
TEMPERATURE	-35 °C to +90°C
SAFETY FACTOR	3 : 1
COLOR	White marking with text "SAFEFLEX OIL SUCTION & DISCHARGE 10 BAR"

ID	OD	MTR/ROLL	MAX WP	TEST PRESSURE	WEIGHT	BR
(INS)	(MM)		(PSI)	(PSI)	(KG/M)	(MM)
1	35	60	150	225	0.75	112
1 - 1/4	44	60	150	225	1.12	144
1 - 1/2	50	60	150	225	1.22	171
2	64	60	150	225	1.96	230
2 - 1/2	79	60	150	225	2.78	290
3	92	60	150	225	3.32	360
4	122	60	150	225	6.03	510
5	148	60	150	225	7.70	635
6	174	30	150	225	10.66	1270
8	228	20	150	225	15.57	1120
10	286	20	150	225	26.00	1530