

OIL SUCTION & DISCHARGE DOCK HOSE

300PSI EN1765/S15



Crude oil and liquid petroleum products suction and delivery to/from tankers and bunkering vessels. Max 55% aromatic content resistance.

| | |
|----------------------|---|
| INNER TUBE | Seamless oil resistant nitrile rubber |
| OUTER COVER | Weather and abrasion resistant neoprene rubber |
| REINFORCEMENT | High tensile textile cords with embedded steel helix wire |
| TEMPERATURE | -30 °C to +85°C |
| SAFETY FACTOR | 3 : 1 |
| COLOR | White marking with text "SAFEFLEX OIL SUCTION & DISCHARGE 20 BAR" |

| ID | OD | MTR/ROLL | MAX WP | TEST PRESSURE | WEIGHT | BR |
|-------|------|----------|--------|---------------|--------|------|
| (INS) | (MM) | | (PSI) | (PSI) | (KG/M) | (MM) |
| 4 | 126 | 60 | 300 | 450 | 6.35 | 850 |
| 6 | 152 | 40 | 300 | 450 | 11.13 | 1000 |
| 8 | 237 | 30 | 300 | 450 | 16.32 | 1500 |
| 10 | 289 | 20 | 300 | 450 | 21.64 | 2000 |
| 12 | 347 | 20 | 300 | 450 | 30.94 | 2500 |