

# CAMLOCKS - ALUMINIUM / STAINLESS STEEL

Data / Dimension Sheet:



Type A Camlock - Male Camlock / Female BSP:

DIMENSION	½"	¾"	1"	1¼"	1½"	2"	2½"	3"	4"
(MM)	15	20	25	32	40	50	65	80	100
A	21	21	34	28.5	36	45	56.5	73	96
B	38	38	48	56	60	64	87	73	78
C	32	32	40	48	56	67	83	96	127



Type B Camlock - Female Camlock / Male BSP:

DIMENSION	½"	¾"	1"	1¼"	1½"	2"	2½"	3"	4"
(MM)	15	20	25	32	40	50	65	80	100
A	14	14	24	28	35	51	58	72	98
B	52	52	64	72	73	80	90	94	101
E	32	32	40	48	49	54	59	60	62
G	53	53	60	78	85	96	110	127	156



Type C Camlock - Female Camlock / Male Hosebarb:

DIMENSION	½"	¾"	1"	1¼"	1½"	2"	2½"	3"	4"
(MM)	15	20	25	32	40	50	65	80	100
A	14	14	20	25	31	43	55	67	92
B	92	92	105	118	121	138	155	164	175
D	20	20	26	33	39	52	65	77	103
E	32	32	40	48	49	54	59	60	62
G	53	53	60	78	85	96	110	127	156



Type D Camlock - Female Camlock / Female BSP:

DIMENSION	½"	¾"	1"	1¼"	1½"	2"	2½"	3"	4"
(MM)	15	20	25	32	40	50	65	80	100
A	16	19	26	30	39	50	58	72	98
B	52	52	62	68	71	78	85	91	96
C	32	32	40	48	56	67	83	96	127
E	32	32	40	48	49	54	59	60	62
G	53	53	60	78	85	96	110	127	156



Type E Camlock - Male Camlock / Male Hosebarb:

DIMENSION	½"	¾"	1"	1¼"	1½"	2"	2½"	3"	4"
(MM)	15	20	25	32	40	50	65	80	100
A	14	19	24	28	35	48	58	72	98
B	98	98	110	121	125	140	158	170	182
D	20	20	26	33	39	52	65	77	103
E	40	40	46	53	56	61	65	66	70
G	34	34	38	48	56	66	80	102	132



Type F Camlock - Male Camlock / Male BSP:

DIMENSION	½"	¾"	1"	1¼"	1½"	2"	2½"	3"	4"
(MM)	15	20	25	32	40	50	65	80	100
A	21	21	24	28.5	36	45	56.5	73	98
B	56	56	72	80	84	88	100	106	114
C	32	32	40	48	56	67	96	96	127
E	39	39	48	56	61	62	74	74	79



Type DC Camlock - Dust Cap:

DIMENSION	½"	¾"	1"	1¼"	1½"	2"	2½"	3"	4"
(MM)	15	20	25	32	40	50	65	80	100
B	45	45	54	65	69	80	84	85	94
E	32	32	40	48	49	54	59	60	62
G	53	53	60	78	85	96	110	127	156



Type DP Camlock - Dust Plug:

DIMENSION	½"	¾"	1"	1¼"	1½"	2"	2½"	3"	4"
(MM)	15	20	25	32	40	50	65	80	100
A	21	21	24	29	36	45	57	73	98
B	37	37	44	55	64	68	70	80	80
E	24	24	30	38	41	43	45	52	48